

## DS 205

### Double sided high bonding self adhesive tape

#### • DESCRIPTION

Double sided easy removable adhesive tape, coated with synthetic rubber adhesive and yellow siliconized paper.

#### • PRODUCT APPLICATION

- Carpet fixing,
- Holding exhibition events
- Domestic carpet holding and temporary fixing.
- Lamination
- General mounting

#### • PRODUCT PROPERTIES

- High adhesion to carpets, runners, etc.
- Safe holding
- Very high conformability
- Hand tearable
- Strong initial adhesion strength
- Maximum adhesive strength reached in 20 minutes
- Outstanding adhesion on low energy plastics



**Athens:** 68, Varis Avenue, 166 73 Voula, Greece,  
Tel.: +30 210 899 5388, Fax exports: + 30 210 899 5386  
**Factory:** 3rd km Pr. rd Skala - Atalanti, 352 00 Atalanti,  
Greece, Tel.: +30 223330 23725, Fax exports: + 30 22330  
23756  
info@atlas-tapes.gr, www.atlas-tapes.gr

**EFFECTIVE:** May 2016

## TECHNICAL DATA SHEET

#### • NOMINAL VALUES

<b>Backing</b>	Carrier: Polypropylene Liner: Silicone paper
<b>Adhesive</b>	Synthetic Rubber based
<b>Tensile Strength MD</b> TM 5004 by Afera	100 ± 20 (N/25mm)
<b>Elongation at Break MD</b> TM 5004 by Afera	120 ± 20 (%)
<b>Adhesion to Steel</b> TM 5001 by Afera	18 ± 2 (N/25mm)
<b>Shear to Steel</b> TM 5012 by Afera	Over 150 (h, 25mm x 25mm on stainless steel, 23°C)
<b>Temperature Range</b>	-10 °C to +75 °C
<b>Total thickness</b>	95 ± 20 (µm)
<b>Adhesive Color</b>	White

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.

